

PressurePro Machine Protector RM 110

For protection against lime deposits in the heating coil system (up to 150 °C) of hot water high-pressure cleaners. Ideal for use with medium to hard water.

pH 9
in concentrate



Properties

- Comprehensive protection and care for hot water high-pressure cleaners
- Effectively protects the heating coil from calcifying
- Quick oil and water separation in the oil separator (easily separable = asf)
- Tensides biodegradable in accordance with EEC 648/2004
- Phosphate-free
- NTA-free

Usage options

- Hot water high-pressure cleaners

Application areas

Agriculture	Transport and machines
Car dealership and garage	Car/engine wash
Building Industry	Transport and machines
Metalworking industry	Degreasing, phosphating
Industry	Surface degreasing
Municipal	Car/engine wash
Haulage contractors, bus operators	Car/engine wash
Machine protector	Machine maintenance, limescale protection

Technical data

Container sizes	Packaging unit	Part number
1 l	6 Piece(s)	6.295-932.0
1 l	6 Piece(s)	6.295-312.0
1 l	6 Piece(s)	6.295-621.0
1 l	6 Piece(s)	6.295-622.0
10 l	1 Piece(s)	6.295-303.0
20 l	1 Piece(s)	6.295-488.0
200 l	1 Piece(s)	6.295-305.0

Application

Hot water high-pressure cleaners

- Set the dosage according to the water hardness (done by service technician).
- Pour the product into the calcification protection tank.

Instructions for use

- Store away from frost.

Further information

- Material Safety Data Sheet (MSDS)

Dosage and yield

Contents	Cleaning method	Dosage	Yield
1000 ml	Hot water high-pressure cleaners	6 ml/°dH m ³	8300 l